



LED Fluorescent Tube

Luminous Efficiency Max 161.5lm/W

CRI

Ra80



Model Name	T8 Series		T5 Series	
	NT40-65NA	ND40-65NA	NDT5-16-65NA	NDT5-20-65NA
Tube Diameter	φ26.0mm(T8)	φ26.0mm(T8)	Φ15.5mm(T5)	Φ15.5mm(T5)
Power consumption	16W	13W	16W	20W
Luminous Flux	2100lm	2100lm	2100lm	3500lm
Weight	260g	233g	160g	180g
Beam Angle	160°	160°	160°	160°
CRI	Ra80	Ra80	Ra80	Ra80
Operating Temperature	-20°C~50°C	-20°C~50°C	-20°C~50°C	-20°C~50°C
Color Temperature	6500K	6500K	6500K	6500K
Input voltage	AC220V~AC240V	AC100V~AC240V	AC220V~AC240V	AC100V~AC240V
Life span	50000h	50000h	50000h	50000h
Warranty	3 Years	3 Years	3 Years	3 Years

Development & Manufacture

Contact Us



Kanto office 1503-1, Osone, Yashio, Saitama-pref, Japan. P.O 340-0834
TEL.+81-48-951-1041 FAX.+81-48-951-1042

Head office 2-20, Motourayashiki, Kadonowakiaza, Ishinomaki,
Miyagi-pref, Japan. P.O 986-0853

Thailand office 87/125-128 Modern Town Tower, Building A, 8th Fl.,
Sukhumvit 63 Rd., North Klongton, Wattana, Bangkok
10110 Thailand