


EVERFINE GONIOPHOTOMETERS SYSTEM TEST REPORT

LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:220.44V I:0.3067A P:65.1W PF:0.9705 Freq:49.99Hz UTHDi:0% ITHDi:0% Lamp Flux:9150 lm					
NAME: SNB70-30ST / SNW70-30ST			TYPE: A		WEIGHT:
SPEC.: 70W			DIM.:		SERIAL No.:
MFR.: EVERFINE			SUR.:		Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 140.6 lm/W
MODEL	SNB70-30ST-A	I _{max} (cd)	7728	S/MH (C0/180)	0.94	
NOMINAL POWER (W)	65.1	LOR (%)	100.0	S/MH (C90/270)	0.97	
RATED VOLTAGE (V)	220	TOTAL FLUX (lm)	9150	η UP, DN (C0-180)	0.3, 48.5	
NOMINAL FLUX (lm)	9150	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.3, 50.9	
LAMPS INSIDE	1	η up (%)	0.6	CIBSE SHR NOM	1.00	
TEST VOLTAGE (V)	220	η down (%)	99.4	CIBSE SHR MAX	1.00	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: li yan feng
Test Date: 05 March 2025

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-SPEX500_V1 SYSTEM V2.00.426
Humidity: 65.0%
Test Distance: 3.270m [K=1.0000]
Remarks: